



Acciaio/Steel: X82WMoV65 (M2)
 Durezza/Hardness: HRC 60/64
 Tolleranza/Tolerance
 Tondi/Round P: +0,01
 0
 Sagome/Shape P,W: +0,02
 0

Chiavetta standard 0° come in figura; disponibile a 90° ,180° ,270° con sovrapprezzo
 Standard flat location is at 0° as shown; available at 90° ,180° ,270° with some alteration price
 Per alterazioni standard v. pagg.:
 For standard alterations see pages:
 Figure EDM v. pag.:
 EDM shape see pag.:

| D | B | R | TONDI | | SAGOME | | L | | | | | | | |
|----|----|----|--------|--------|--------|---------|----|----|----|----|----|----|----|----|
| | | | D1 min | D1 max | W min | P/G max | 20 | 22 | 25 | 28 | 30 | 32 | 35 | 40 |
| 6 | 3 | 4 | 2,00 | 3,50 | 2,00 | 3,50 | ● | ● | ● | ● | ● | ● | ● | |
| 10 | 4 | 6 | 2,00 | 5,50 | 2,00 | 5,50 | ● | ● | ● | ● | ● | ● | ● | |
| 13 | 4 | 8 | 2,00 | 7,50 | 2,00 | 7,50 | ● | ● | ● | ● | ● | ● | ● | |
| 16 | 4 | 9 | 5,00 | 8,50 | 2,50 | 8,50 | ● | ● | ● | ● | ● | ● | ● | |
| 20 | 4 | 12 | 5,50 | 11,00 | 3,20 | 11,00 | ● | ● | ● | ● | ● | ● | ● | |
| 22 | 6 | 14 | 7,50 | 13,50 | 4,00 | 13,50 | ● | ● | ● | ● | ● | ● | ● | |
| 25 | 6 | 17 | 9,50 | 16,50 | 4,80 | 16,50 | ● | ● | ● | ● | ● | ● | ● | |
| 32 | 6 | 21 | 13,00 | 20,50 | 5,50 | 20,50 | ● | ● | ● | ● | ● | ● | ● | |
| 38 | 8 | 27 | 16,00 | 26,50 | 6,40 | 26,50 | ● | ● | ● | ● | ● | ● | ● | |
| 40 | 8 | 27 | 16,50 | 26,50 | 6,40 | 26,50 | ● | ● | ● | ● | ● | ● | ● | |
| 45 | 12 | 36 | 19,00 | 35,00 | 7,50 | 35,00 | | ● | ● | ● | ● | ● | ● | ● |